







WINCH SPECIFICATIONS

LINE PULL
- LOW SPEED - 30000 LBS @ AVE LAYER
- HIGH SPEED - 8100 LBS AVE LAYER

LINE SPEED
- LOW SPEED - 140 FT PER MIN. @ AVE LAYER
- HIGH SPEED - 600 FT PER MIN @ AVE LAYER

DRUM CAPACITY
- 45000 FT OF 1/2 DIA WIRE ROPE

WINCH CONTROL
- ELECTRIC - LOCAL & REMOTE

POWER
- ELECTRO - HYDRAULIC

POWER PACK
- 250 H.P. 440 VOLT, 3 PHASE, 60 HERTZ

HYDRAULIC OIL RESERVOIR CAPACITY

COOLING WATER FEED
- 65 GPM (SEA WATER)

WEIGHT
- DRY -
- WET -

2

ITEM FIND NO	REQD QTY	CODE IDENT NO.	DRAWING NUMBER	PART OR IDENTIFYING NUMBER	NOMENCLATURE OR DESCRIPTION	MATERIAL	EQUIVALENT OR MFR SPECIFICATION

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON
FRACTIONS ±
DECIMALS .X ± 1, .XX ± .05, .XXX ± .010
ANGLES ± 0° 30'
SURFACE FINISH MICROINCHES
DO NOT SCALE

CONTRACT OR PROJECT NO

NORTHERN LINE MACHINE & ENGINEERING CO.
DIVISION OF TACOMA BOATBUILDING CO., INC.
1840 MARINE VIEW DRIVE TACOMA, WASHINGTON 98422

DRAWN STEVE 6-21-77
CHECK
ENGR

GENERAL ARRANGEMENT CORING WINCH

NEXT ASSY USED ON
MODEL NO.
APPLICATION

SIZE F | CODE IDENT NO 25511 | DRAWING NUMBER GYRE-0083

SCALE 1"= 1" | WEIGHT | SHEET 1 OF

REVISIONS

ZONE	ITEM	DESCRIPTION	DATE	BY