

SILOO INCORPORATED -- SILOO DIESEL FUEL CONDITIONER -- 6850-00N006170

=====
Product Identification
=====

Product ID:SILOO DIESEL FUEL CONDITIONER

MSDS Date:01/01/1985

FSC:6850

NIIN:00N006170

MSDS Number: BCMCW

=== Responsible Party ===

Company Name:SILOO INCORPORATED

Emergency Phone Num:212-695-3190

CAGE:HO222

=== Contractor Identification ===

Company Name:SILOO

Box:2549

City:WARMINSTER

State:PA

ZIP:18974

Country:US

Phone:215-674-4300

CAGE:54037

Company Name:SILOO INCORPORATED

CAGE:HO222

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 9%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt: 78%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 8990

Ingred Name:GLYCOL ETHER

CAS:111-46-6

RTECS #:ID5950000

Fraction by Wt: 3%

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: 10%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

=====
===== Hazards Identification =====

Effects of Overexposure:EYE: IRRITATION. SKIN: DEFATTING,IRRITATION.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER 15 MINUTES. SKIN: WASH WITH SOAP AND WATER,REMOVED CONTAMINATED CLOTHING.

=====
===== Fire Fighting Measures =====

Flash Point:192F/88C (TCC)

Extinguishing Media:CO*2

Fire Fighting Procedures:SELF-CONTAIN BREATH APP,HANDLE AS WITH DIESEL FUEL.

=====
===== Accidental Release Measures =====

Spill Release Procedures:HANDLE AS WITH SPILLED DIESEL FUEL,KEROSENE,ETC.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AS WITH DIESEL FUEL.

=====
===== Exposure Controls/Personal Protection =====

Ventilation:MECHANICAL

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:244F/117C

Vapor Pres:2

Spec Gravity:0.7724

Evaporation Rate & Reference:0.21 (BUACETATE)

Solubility in Water:MODERATE

Appearance and Odor:LIGHT AMBER LIQUID,CLEAR,TRANSLUCENT.

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

=====
Disposal Considerations
=====

Waste Disposal Methods:COMPLY WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.