



## **5. REACTIVITY DATA**

STABILITY: STABLE  
CONDITIONS TO AVOID  
Do not heat above flash point

HAZARDOUS DECOMPOSITION OR BYPRODUCTS  
Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

## **6. HEALTH HAZARD DATA**

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
Inhalation of vapors or oil mist from this product may cause mild irritation, which may lead to various skin disorders. Avoid prolonged skin contact.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
SKIN-repeated or prolonged contact with skin may cause irritation, which may lead to various skin disorders. Avoid prolonged skin contact.  
EYES-may cause irritation if splashed into eyes

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
Ingestion may cause nausea, diarrhea and stomach discomfort.

HEALTH HAZARDS (ACUTE AND CHRONIC)  
Acute – depending on degree of exposure material may cause eye, nose, respiratory tract, and skin irritation. Headache, nausea are also symptoms of overexposure chronic- intentional abuse, misuse, or massive exposure may lead to muscular weakness, confusion, impaired coordination, liver and kidney damage, dermatitis or may cause multiple organ damage an/or may even cause death.

CARCINOGENICITY: NTP CARCINOGEN: No            IARC Monographs: No  
OSHA REGULATED: No  
Not carcinogenic

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE  
Respiratory conditions, pre-existing skin disorders, liver or kidney disease

## **7. EMERGENCY AND FIRST AID MEASURES**

Eyes Contact – Flush with water at least 15 min. get medical attention if eye irritation develops or persists.

Skin Contact – Wash immediately with soap and water. Remove soiled clothing. Get medical attention if irritation develops. Launder contaminated clothing.

Ingestion – Do not induce vomiting; if conscious, give 2 glasses of water. Get immediate medical attention.

Inhalation – Remove to fresh air, restore breathing if necessary. Treat symptoms. Get immediate medical attention.

## **8. PRECAUTIONS FOR SAFE HANDLING AND USE**

### **STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Evacuate all non-essential personnel. Personal protective equipment must be worn, see PPE section 8 & 16. Remove sources of ignition. Prevent entry into sewers and waterways. Contain release. Pick up free liquid for recycling or disposal. Residual liquid can be absorbed with inert material. Check DOT/CERCLA and other agencies for reporting requirements.

### **WASTE DISPOSAL METHOD**

Dispose of material in a manner approved by local, state and federal regulations. Before attempting cleanup, refer to hazard caution information in other sections of this sheet.

### **PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Handling – Avoid prolonged skin contact, breathing vapors, and contaminated clothing. Use with adequate ventilation. Wear recommended protective equipment. Practice good personal hygiene after handling.

Storage – Store in closed containers of proper construction. Store away from ignition sources and in areas of good ventilation.

### **OTHER PRECAUTIONS**

Warning – detectable amounts of chemicals known to the State of California to cause cancer, birth defects, or other reproduction harm may be found in this product. Proposition 65 California Health & Safety Code – section 25249.9 THIS MATERIAL IS FOR INDUSTRIAL USE ONLY. MATERIAL SHOULD ONLY BE USED AFTER ALL SAFETY PRECAUTIONS ARE READ AND UNDERSTOOD BY EVERYONE HANDLING MATERIAL. Do not weld or flame-cut and empty container. Keep away from children.

## **9. CONTROL MEASURES**

### **RESPIRATORY PROTECTION**

Use NIOSH/MSHA approved respirator with organic vapor cartridge and dust/ mist cartridge if recommended exposure limit is exceeded. Self-contained breathing apparatus is recommended for confined space entry.

### **VENTILATION**

Use in area of adequate ventilation. Use mechanical exhaust to control vapors or mists.

### **PROTECTIVE GLOVES**

Use nitrile or neoprene gloves are recommended.

### **EYE PROTECTION**

Safety glasses or goggles are recommended

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Long sleeve shirt and apron when potential for skin contact. Wear neoprene or nitrile rubber boots when necessary to avoid contaminating shoes.

## 10. TRANSPORTATION AND STORAGE

DOT shipping name: Oil, n.o.s.  
DOT Hazard Class: not regulated  
UN/NA Number: NA 1270  
Guide Number: 27  
IMDG Code:

Materials classified as DOT combustible liquids (Flash point > 141F and < 200F) are not regulated by DOT in containers of 110 gallons, or less for domestic shipments.

## 11. DISCLAIMER

Parker Hannifin Corp./Racor -Village Marine Tec makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Parker Hannifin Corp./Racor -Village Marine Tec as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Parker Hannifin Corp./Racor -Village Marine Tec assume liability arising out of the use by others of this product referred to herein. The data in this MSDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. This MSDS relates only to material safety data, not the labeling of a container.

**Prepared by: S. Howard**

**Date: 09/25/2009**

**Revision Number: Initial Release**

**Revision Information: Initial Release**