



Product Data

HEMPEL'S ACRYLIC PRIMER/SEALER 26630

Description: HEMPEL'S ACRYLIC PRIMER/SEALER 26630 is a solvent-borne alkali resistant acrylic primer/sealer with excellent penetration and dust binding properties. For use under solvent-borne as well as under water-borne coatings.

Area of use: **Interior and exterior:** Walls, ceilings, partitions, etc.

Substrates: Concrete, masonry, cement rendering, plaster, gypsum, wood, etc.

PHYSICAL CONSTANTS:

Colour/Shade nos:	White/10000		
Finish:	Flat		
Volume solids, %:	33 ± 1		
Theoretical spreading rate	11.0 m ² /litre - 30 micron*		
Specific gravity:	1.1 kg/litre		
Dry to touch:	2 hours (10 °C)	1 hour (20 °C)	30 minutes (40 °C)
Flash point:	43°C		

**The spreading rate has been calculated theoretically for application onto a primed and smooth surface. The actual rates may differ significantly as the primer/sealer is intended to be applied to rough and porous substrates. The actual rates will also depend on the extent of thinning, the application method and the relevant consumption factor.*

The physical constants stated are nominal data according to the HEMPEL Group's approved formulas. They are subject to normal manufacturing tolerances and where stated, being standard deviation according to ISO 3534-1.

APPLICATION DETAILS:

Application method:	Brush/roller Conventional spray		
Thinner (max. vol.):	08080 (15%) 08080 (30%)		
Cleaning of tools:	THINNER 08080		
Recoat interval, min:	2 hours (10 °C)	1 hour (20 °C)	30 minutes (40 °C)
Recoat interval, max:	None	None	None

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, laitance, dirt, grease and oil.

Remarks: Drying data given is on the assumption that proper ventilation is provided.
Note: **HEMPEL'S ACRYLIC PRIMER/SEALER 26630 is for professional use only.**

Safety: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult HEMPEL Material Safety Data Sheets and follow all local or national safety regulations. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosions as well as protection of the environment. Apply only in well ventilated areas.

ISSUED BY: HEMPEL A/S - 2663010000CS007

This Product Data Sheet supersedes those previously issued.

For explanations, definitions and scope, see "Explanatory Notes" in the HEMPEL Book.

Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User.

The Products are supplied and all technical assistance is given subject to HEMPEL's GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving, any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise.

Product data are subject to change without notice and become void five years from the date of issue.