

TLA856_A3

Material Safety Data Sheet INTERLINE 850 CONVERTER

Sales
Order: {SalesOrd}
TLA856
06/28/2008
A3-0

Bulk Sales Reference No.:
MSDS Revision Date:
MSDS Revision Number:



1. Identification of the preparation and company

Product Identity INTERLINE 850 CONVERTER
Bulk Sales Reference No. TLA856
Company Name International Paint LLC
6001 Antoine Drive
Houston Texas 77091

Emergency
CHEMTREC (USA) (800) 424-9300
International Paint (713) 527-3887
Poison Control Center (800) 854-6813
Customer Service
International Paint (800) 589-1267
Interlux (800) 631-7481

2. Hazard identification of the product



Danger

GHS Classification;

Item	Category	Hazard
Flammability	3	Flammable liquid and vapor
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	2	Causes skin irritation
Eye damage/irritation	1	Causes serious eye damage
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	1	May cause allergic reaction.
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	Not applicable
	2	Not applicable
	3	narcotic effects, respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	auditory apparatus, central nerve system
	2	Not applicable
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	Not classified	Not applicable
Harmfulness to aquatic Environment (long term effect)	Not classified	Not applicable

TLA856_A3

Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases:

- S1: Keep locked up.
- S9: Keep container in a well-ventilated place.
- S20: When using do not eat or drink.
- S23: Do not breathe vapor/spray.
- S24: Avoid contact with skin.
- S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S27: Take off immediately all contaminated clothing.
- S28: After contact with skin, wash immediately with plenty of soap and water.
- S37: Wear suitable gloves.
- S39: Wear eye/face protection.
- S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- S46: If swallowed, seek medical advice immediately and show this container or label.
- S51: Use only in well-ventilated areas.
- S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.		
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.		
Eyes	May cause severe eye damage. Avoid contact with eyes.		
Skin	Causes skin irritation. May cause delayed skin irritation. May be harmful if absorbed through the skin.		
Ingestion	May be fatal or cause blindness if swallowed. Cannot be made non-poisonous. Can result in irritation of the mouth, stomach tissue and digestive tract.		
Chronic effects			
HMIS Rating	Health: 3	Flammability: 2	Reactivity: 0

3. Composition/information on ingredients

Ingredient	CAS No.	Percent
Butanol	000071-36-3	10 - 25
2,4,6-Tri(dimethylaminomethyl)phenol	000090-72-2	1.0 - 10
Benzyl alcohol	000100-51-6	1.0 - 10
Diethylene triamine	000111-40-0	1.0 - 10
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	068609-97-2	10 - 25

4. First aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

TLA856_A3

5. Fire-fighting measures

Flash Point F: 129
C: 54

Lower Explosive Limit (LEL) 1 (%vol in air) at Normal Atmospheric Temp and Pressure

ERG Guide No. 127

6. Accidental release measures

Spill Response Procedures ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

Public Safety CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

ERG Guide No. 127

7. Handling and storage

Storage Temperature Store between 32 and 120 F

Handling and Storage Precautions Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection

Exposure

CAS No.	Ingredient	Source	Value
000071-36-3	Butanol	OSHA	100 ppm TWA; 300 mg/m3 TWA50 ppm Ceiling; 150 mg/m3 Ceiling
		ACGIH	20 ppm TWA
		NIOSH	50 ppm Ceiling; 150 mg/m3 Ceiling1400 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	20 ppm TWAEV
		Mexico	No Established Limit
		Brazil	No Established Limit
000090-72-2	2,4,6-Tri(dimethylaminomethyl)phenol	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
000100-51-6	Benzyl alcohol	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

TLA856_A3

		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
000111-40-0	Diethylene triamine	OSHA	No Established Limit
		ACGIH	1 ppm TWA
		NIOSH	1 ppm TWA; 4 mg/m3 TWA
		Supplier	No Established Limit
		OHSA, CAN	1 ppm TWAEV; 4 mg/m3 TWAEV
		Mexico	1 ppm TWA; 4.2 mg/m3 TWA
		Brazil	No Established Limit
068609-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
000071-36-3	Butanol	NIOSH	Eye and mucous membrane irritation CNS depression
000090-72-2	2,4,6-Tri(dimethylaminomethyl)phenol	NIOSH	No Established Limit
000100-51-6	Benzyl alcohol	NIOSH	No Established Limit
000111-40-0	Diethylene triamine	NIOSH	Skin and respiratory irritation and sensitization
068609-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
000071-36-3	Butanol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
000090-72-2	2,4,6-Tri(dimethylaminomethyl)phenol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
000100-51-6	Benzyl alcohol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
000111-40-0	Diethylene triamine	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
068609-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator

TLA856_A3

(NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Physical State	Liquid
pH	Not Determined
Specific Gravity	0.96
Boiling Point F	243
Vapor Density	Heavier than air
VOC %	Refer to the Technical Data Sheet for this product
Evaporation Rate	Slower than ether

10. Stability and reactivity

General	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
Incompatible Materials	Strong oxidizing agents.
Hazardous Decomposition	May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr
Butanol – (000071-36-3)	790.00, Rat – Category: 4	3,400.00, Rabbit – Category: 5	17.70, Rat – Category: 4
2,4,6-Tri(dimethylaminomethyl)phenol – (000090-72-2)	1,000.00, Rat – Category: 4	1,280.00, Rat – Category: 4	-----
Benzyl alcohol – (000100-51-6)	1,230.00, Rat – Category: 4	2,000.00, Rabbit – Category: 4	8.80, Rat – Category: 3
Diethylene triamine – (000111-40-0)	819.00, Rat – Category: 4	672.00, Rabbit – Category: 3	-----
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. – (068609-97-2)	17,100.00, Rat – Category: NA	-----	-----

General	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8
---------	--

and 11 for chemical specific data.

12. Ecological information

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)	
DOT Proper Shipping Name	PAINT	IMDG Proper Shipping Name	PAINT
DOT Hazard Class	3	IMDG Hazard Class	3.3 – High flashpoint flammable liquids
UN / NA Number	UN 1263	UN / NA Number	UN 1263
DOT Packing Group	III	IMDG Packing Group	III
CERCLA/DOT RQ	5301 gal. / 42265 lbs.	System Reference Code	1

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B3; D2B; E

DOT Marine Pollutants (10%):
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :
Butanol (5000 lb final RQ; 2270 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :
Butanol

Mass RTK Substances (>1%) :
Benzyl alcohol
Diethylene triamine
Butanol

Mass Extraordinarily Haz Sub (>.01%) :
(No Product Ingredients Listed)

Penn RTK Substances (>1%) :
Benzyl alcohol
Diethylene triamine
Butanol

Penn Special Hazardous Substances (>.01%) :
(No Product Ingredients Listed)

Rhode Island Hazardous Substances (>.1%) :
Diethylene triamine
Butanol

RCRA Status:
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :
Diethylene triamine

Butanol

N.J. Special Hazardous Substances (>.01%) :

Diethylene triamine

Butanol

Tetraethylenepentamine

Triethylene tetramine

N.J. Env. Hazardous Substances (>.1%) :

Butanol

Proposition 65 – Carcinogens (>0%):
(No Product Ingredients Listed)

Proposition 65 – Female Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 – Male Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 – Developmental Toxins (>0%):
(No Product Ingredients Listed)

Risk Phrases:

R22: Harmful if swallowed.

R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.