

**SIGMACOVER 510 (SIGMA TCN TIECOAT) BASE**

Version 5.4

Print Date 10/25/2004

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING****Product information**

**Trade name** : SIGMACOVER 510 (SIGMA TCN TIECOAT) BASE  
**Technical data sheet number** : 7479

**Company** : Sigma Coatings BV  
 Amsterdamseweg 14  
 1422 AD Uithoorn

**Telephone** : +31297541911

**Telefax** : +31297541050

**Emergency telephone number** : +31204075210

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

Components	EINECS No	CAS-No.	Symbol(s)	R-phrases(s)	Concentration
xylene	215-535-7	1330-20-7	Xn	R10, R20/21, R38	2.50 - 10.00%
ethylbenzene	202-849-4	100-41-4	F, Xn	R11, R20	0.00 - 2.50%
epoxy resin (MW <=700)		25068-38-6	Xi, N	R36/38, R43, R51/53	2.50 - 10.00%
1-METHOXY-2-PROPANOL	203-539-1	107-98-2		R10	10.00 - 25.00%
Creosote oil, acenaphthalene fraction	292-605-3	90640-84-9	T	R45	0.00 - 2.50%
Pitch, coal tar, high-temp.	266-028-2	65996-93-2	T	R45	10.00 - 25.00%
Distillates (coal tar), heavy oils	292-607-4	90640-86-1	T	R45	0.00 - 2.50%

*For components with an occupational treshold limit value see chapter 8.*

**3. HAZARDS IDENTIFICATION****Toxic****Hazardous components :**

Pitch, coal tar, high-temp.  
 epoxy resin (MW <=700)  
 Creosote oil, acenaphthalene fraction  
 Distillates (coal tar), heavy oils

**R-phrase(s) :**

MAY CAUSE CANCER.  
 FLAMMABLE.  
 IRRITATING TO EYES AND SKIN.  
 MAY CAUSE SENSITIZATION BY SKIN CONTACT.  
 HARMFUL TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.

**S-phrase(s) :**

Avoid exposure - obtain special instructions before use.

**SIGMACOVER 510 (SIGMA TCN TIECOAT) BASE**

Version 5.4

Print Date 10/25/2004

Do not breathe spray.  
 Wear suitable protective clothing and gloves.  
 In case of insufficient ventilation, wear suitable respiratory equipment.  
 In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).  
 Avoid release to the environment. Refer to special instructions/safety data sheets.

**P-phrase(s) :**

Contains epoxy constituents. See information supplied by the manufacturer.  
 Restricted to professional users. Attention - Avoid exposure - obtain special instructions before use.

**Note** : The information required is contained in this Material Safety Data Sheet.

**4. FIRST AID MEASURES**

- General advice** : When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.
- Eye contact** : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. Remove contact lenses. Seek medical advice.
- Skin contact** : Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Inhalation** : Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.
- Ingestion** : If accidentally swallowed obtain immediate medical attention. Keep at rest. Do not induce vomiting.

**5. FIRE-FIGHTING MEASURES**

- Specific hazards during fire fighting** : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters** : In the event of fire, wear self-contained breathing apparatus.
- Suitable extinguishing media** : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Keep containers and surroundings cool with water spray.
- Extinguishing media which must not be used for safety reasons** : Do NOT use water jet.

**6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions** : Use personal protective equipment. Ventilate the area. Refer to protective measures listed in sections 7 and 8. Wear respiratory protection. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Remove all sources of ignition.
- Environmental precautions** : Try to prevent the material from entering drains or water ways. If the product contaminates rivers and lakes or drains inform respective authorities.

**SIGMACOVER 510 (SIGMA TCN TIECOAT) BASE**

Version 5.4

Print Date 10/25/2004

- Methods for cleaning up** : Clean with detergents. Avoid solvents. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- Additional advice** : Refer to section 15 for specific national regulation.

**7. HANDLING AND STORAGE****Handling**

- Safe handling advice** : Avoid exceeding of the given occupational exposure limits (see section 8). Use only in area provided with appropriate exhaust ventilation. Avoid contact with skin, eyes and clothing. Smoking, eating and drinking should be prohibited in the application area. Avoid inhalation of vapour or mist. For personal protection see section 8.
- Advice on protection against fire and explosion** : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. When transferring from one container to another apply earthing measures and use conductive hose material. No sparking tools should be used. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. No smoking. The accumulation of contaminated rags and dry overspray, particularly in spray booth filters, may result in spontaneous combustion. Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

**Storage**

- Requirements for storage areas and containers** : Observe label precautions. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store between 5 and 25°C (41 - 77 F) in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Electrical installations / working materials must comply with the technological safety standards. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations (see section 15).
- Advice on common storage** : Keep away from oxidising agents and strongly acid or alkaline materials.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Minimum ventilated air quantity for 1 liter of product**

- TO REACH TLV** : 1,269 m<sup>3</sup>/l Basis: MAC (NL)
- TO REACH 10 % LEL** : 64 m<sup>3</sup>/l
- TLV of the product** : 274 mg/m<sup>3</sup> Basis: MAC (NL)

**Components with workplace control parameters**

Components	CAS-No.	Value [mg/m <sup>3</sup> ]	Value [ppm]	Basis

**SIGMACOVER 510 (SIGMA TCN TIECOAT) BASE**

Version 5.4

Print Date 10/25/2004

xylene <i>can be absorbed through skin</i> <i>can be absorbed through skin</i>	1330-20-7	210.00 221.00 442.00	50.00 50.00 100.00	MAC (NL) TWA EU ELV TWA EU ELV STEL
ethylbenzene <i>can be absorbed through skin</i> <i>can be absorbed through skin</i>	100-41-4	215.00 442.00 884.00	50.00 100.00 200.00	MAC (NL) TWA EU ELV TWA EU ELV STEL
1-METHOXY-2-PROPANOL <i>can be absorbed through skin</i>	107-98-2	375.00 375.00 568.00	100.00 100.00 150.00	MAC (NL) TWA EU ELV TWA EU ELV STEL

**Personal protective equipment****General advice**

- Respiratory protection** : When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
- Hand protection** : For prolonged or repeated contact use protective gloves. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Skin should be washed after contact.
- Eye protection** : Chemical resistant goggles must be worn.
- Skin and body protection** : Personnel should wear protective clothing. Skin should be washed after contact. Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire. Workers should wear antistatic footwear.

**Additional advice**

- :  
: SigmaKalon Internal Safety Code (INSACO)  
: Special work instructions

*Please contact your personal protection equipment supplier for further advice*

**9. PHYSICAL AND CHEMICAL PROPERTIES**

- Form** : viscous
- Colour** : various
- Odour** : characteristic
- Flash point** : 26.8 °C  
Note: Calculated
- Autoignition temperature** : > 270 °C
- Lower explosion limit** : 1.34 %(V)
- Density** : 1.46 g/cm<sup>3</sup>  
at 20 °C
- Water solubility** : immiscible
- Viscosity, dynamic** : 2,000 mPa.s at 23 °C

**SIGMACOVER 510 (SIGMA TCN TIECOAT) BASE**

Version 5.4

Print Date 10/25/2004

**Flow time** :  $\geq 60$  s  
Transversal section: 6 mm  
Method: ISO 2431 (EN 535) 6 mm CUP

**10. STABILITY AND REACTIVITY**

**Conditions to avoid** : Avoid temperatures above 60°C (140 F), direct sunlight and contact with sources of heat.

**Hazardous reactions** : Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**Hazardous decomposition products** : In case of fire hazardous decomposition products may be produced such as: Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke. Burning produces obnoxious and toxic fumes.

**11. TOXICOLOGICAL INFORMATION**

**Acute oral toxicity** : May cause nausea, abdominal spasms and irritation of the mucous membranes.

**Acute inhalation toxicity** : Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects. Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

**Skin irritation** : Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in desiccation of the skin. The product may be absorbed through the skin. Repeated skin contact may lead to irritation and to sensitization, possible with cross-sensitization to other epoxies.

**Eye contact** : May cause irreversible eye damage.

**Carcinogenicity** : Note: High standards of skin care and personal hygiene should be exercised at all times. Medical advice should be sought without delay if warts appear. Prolonged and repeated contact with the skin can lead to the development of warts. These can take various forms. A few are cancerous. These can be cured with early treatment. Based on the properties of the coal tar in this product, skin contact should be avoided preferably by use of a closed system. Where this is not possible, protective clothing, gloves and face shields should be used to protect bare skin.

**Further information** : There is no data available for this product.

**12. ECOLOGICAL INFORMATION**

**Further information** : The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for ecotoxicological properties accordingly. See sections 2 and 15 for details.

**13. DISPOSAL CONSIDERATIONS**

**Product** : The product should not be allowed to enter drains, water courses or the soil. Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

**SIGMACOVER 510 (SIGMA TCN TIECOAT) BASE**

Version 5.4

Print Date 10/25/2004

**14. TRANSPORT INFORMATION**

Transport to be in accordance with ADR for road, IMDG for sea and IATA for air transport:

UN-No : 1263  
 Proper shipping name : PAINT  
 Class : 3  
 Packing group : III  
 Label : 3

Marine Pollutant (IMDG)(P,PP,-) : -  
 EmS (IMDG) : F-E, S-E

Limited quantity (ADR) : Max. per inner pack. : 5.00 L  
 Max. per outer pack. : 45.00 L  
 Limited quantity (IMDG) : Max. per inner pack. : 5.00 L  
 Max. per outer pack. : 30.00 KG

**Note**

If pack sizes less than 450L, under the terms of 2.2.3.1.5, this product is not subject to the provisions of ADR.

If pack sizes up to and including 30L, under the terms of 2.3.2.5, this product is not subject to the packaging, labelling and marking requirements of the IMDG code, but both full documentation and placarding of cargo transport units is still required.

**15. REGULATORY INFORMATION**

**Remarks** : *A hard copy of the label is placed in section 3*

**Note** : The information required is contained in this Material Safety Data Sheet.

**Hazardous components which must be listed on the label:**

- Pitch, coal tar, high-temp.
- epoxy resin (MW <=700)
- Creosote oil, acenaphthalene fraction
- Distillates (coal tar), heavy oils

**Symbol(s)** : T Toxic

**R-phrases(s)** : R45 May cause cancer.  
 R10 Flammable.  
 R36/38 Irritating to eyes and skin.  
 R43 May cause sensitization by skin contact.  
 R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**S-phrases(s)** : S53 Avoid exposure - obtain special instructions before use.  
 S23 Do not breathe spray.  
 S36/37 Wear suitable protective clothing and gloves.  
 S38 In case of insufficient ventilation, wear suitable respiratory equipment.  
 S45 In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).  
 S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

**SIGMACOVER 510 (SIGMA TCN TIECOAT) BASE**

Version 5.4

Print Date 10/25/2004

<b>P-phrase(s)</b>	:	P92 P95	Contains epoxy constituents. See information supplied by the manufacturer. Restricted to professional users. Attention - Avoid exposure - obtain special instructions before use.
<b>VOC</b>	:	354.5 g/l Method: Calculated	
<b>National legislation</b>			
<b>Vlarem</b>	:	P2, T	
<b>CPR Classification</b>	:	K3 T	
<b>NER Classification</b>	:	NER Class O.1: 0 %(m) NER Class O.2: 11.3 %(m) NER Class O.3: 12.9 %(m)	
<b>MAL code (1993)</b>	:	3 - 6	<b>Update</b> : 1993

**16. OTHER INFORMATION**

This product contains a complex mixture of hydrocarbons. Detailed information can be obtained by the producer.

**Explanation of R-phrases mentioned in section 2**

xylene	R10 R20/21 R38	Flammable. Harmful by inhalation and in contact with skin. Irritating to skin.
ethylbenzene	R11 R20	Highly flammable. Harmful by inhalation.
epoxy resin (MW <=700)	R36/38 R43 R51/53	Irritating to eyes and skin. May cause sensitization by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
1-METHOXY-2-PROPANOL	R10	Flammable.
Creosote oil, acenaphthalene fraction	R45	May cause cancer.
Pitch, coal tar, high-temp.	R45	May cause cancer.
Distillates (coal tar), heavy oils	R45	May cause cancer.

Version: 5.4

Revision date 03.06.2004

The information contained in this safety data sheet is based on the present state of knowledge and current national legislation at the date of issue. The company reserves the right to modify data without notice. Any change in data will normally be followed by issue of a new safety data sheet. The user should check the date of issue and if more than 12 months have elapsed, then the data should only be used after checking with our nearest sales office to establish that they are still valid. . As the specific conditions of use of the product are outside the suppliers control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. None of the information



**SIGMACOVER 510 (SIGMA TCN TIECOAT) BASE**

Version 5.4

Print Date 10/25/2004

contained in this safety data sheet can be constructed as a guarantee with regard to the properties of the product described. No liability can be accepted on the basis of this safety data sheet.

After all component(s) stated on the relevant Technical Data Sheet have been mixed the safety precautions mentioned on each of the component(s) safety data sheets and labels should be used in assessing the safety precautions of the mixed product.

For further information see technical data sheet number: 7479